


DOUBLE D ELECTRONICS LTD

DDA219-X90 Dual LNB Power Supply & 1+1 Redundancy Controller

- * Two regulated LNB power supplies
- * Adjustable voltage for LNB supplies
- * LNB current monitoring for faults
- * Adjustable current limits
- * Waveguide Switch interface
- * Automatic redundancy mode
- * Generic front panel
- * Remote Monitoring & Control Port
- * Compatible with other DDA219 variants
- * Redundant Power Supplies
- * RS-232 and RS-422/485 serial ports for RC&M
- * 1U 19" rack mount
- * Summary alarm output
- * Buffered alarm outputs



The DDA219-X90 is a variant of the popular DDA219 general purpose controller for 1+1 switching systems, optimised for LNB applications. It includes two linear power supplies with adjustable voltage level and current thresholds, and overload protection. It also includes automatic redundancy facilities. Its compact size makes it ideal for mobile use, and other applications where space is at a premium.

The unit includes dual mains inlets and supplies for redundancy, feeding an internal power bus. There is a separate output connector for each LNB supply. For LNBs powered via the coaxial cable an external bias tee (not supplied) is required.

The LNB supply voltage, current thresholds and current consumption may be monitored on a test connector at the rear of the unit, and adjustments are accessible through the rear panel.

There are buffered alarm outputs for over and under current for each LNB.

The DDA219-X90 includes a remote monitoring & control port supporting 4-wire RS-485 and RS-232, compatible with the larger DDA70 family as well as the DDA69/DDA78 1+1 controllers.

The front panel provides local control and status. A number of standard front panel mimics can be supplied, with the layout shown on this page being the standard.

SPECIFICATION

- Physical: 19" rack, 1U high, 360mm deep (excluding connectors).
- Power: 90-254V a.c., 48-62Hz, 150VA max. Redundant power feed (dual power supplies) via two IEC mains inlets
- LNB Power: 9-pin D-socket (2 off) - voltage adjustable 12-20V d.c. @ 500mA max. Separately adjustable high and low current thresholds for each LNB.
- Switching: Interface for a single waveguide switch, 24V coils, common negative, including inputs for locks.
- LNB Alarms: 15-pin D-socket; has buffered alarm outputs for each LNB - overcurrent and undercurrent.
- Mute Outputs: 9-pin D-socket per LNB with volt-free changeover contact for muting - active during switching
- Host Serial: 9-pin D-socket; RS-232 and 4-wire RS-422/RS-485, fixed 9600,7,e,1. Supports "Printable ASCII" and "STX/ETX" protocols.
- Summary Alarm: 9-pin D-plug; volt-free relay contact signals alarm on any detected fault.

Ordering Information

DDA219-M90 Dual LNB Power Supply/1+1 Redundancy Controller.

In the above part number, substitute as follows:

M Mimic type:
0 - Standard generic mimic (as previous page)
9 - Remote control unit - PSU indications only

Example: DDA219-090 is a dual LNB power supply with generic mimic.